



EV8383F-B

5 MEGAPIXEL BULLET CAMERA



Model	EV8383F-B
Image Sensor	1/ 2.5" 5 MP
WDR	N/A
Num. of Effective Pixels	2592×1920 H×V
Lens	4~12 mm Varifocal, F1.4
F.O.V. (Horizontal)	78° (wide)~30° (tele)
Minimum Illumination	0.1 Lux, 0 Lux (IR On)
Shutter Time (sec.)	1/3~1/15000 or 1/4~1/15000 Selectable
Auto Iris	DC Drive
S/N Ratio	More than 38 dB
Day/Night	Yes, Built-in ICR, <10Lux IR Enabled
Video Compression	Motion JPEG, MPEG-4, .264 High Profile
H.264/MJPEG	10fps: 5 MP; 20fps: 3 MP; 30fps: HD-1080p, HD-720p, SXGA, 1024 × 768, 800 × 600, D1, VGA, QVGA, QQVGA
MPEG4	30fps: HD-1080p, HD-720p, SXGA, 1024×768, 800×600, D1 VGA, QVGA, QQVGA, Minilux mode
Video Streaming	Multiple Stream: Supports up to 4 independent Streams with ROI (Region of Interest) feature, Controllable Framerate and Bandwidth CBR/VBR
Video Output	SDTV-Composite video
Image Setting	Compression, Brightness, Contrast, Mirroring, Sharpness, AWB, AES, AGC, BLC, Day/Night Mode, WDR, 4Privacy Mask Regions
Audio Compression	G.711, G.726, AAC
Audio Input	Line In × 1
Audio Output	Line Out × 1
Security	Password Protection, IP Address Filtering, User Access Privilege
Network Protocols	TCP/IP, UDP, DHCP, PPPoE, HTTP, HTTPS, DNS, DynDNS, NTP, FTP, SMTP, RTP, RTSP, RCTP, 3GPP, UPnP, IPv4, SAMBA client (NAS), IGMP, ICMP, ARP
Intelligent Video	Video Motion Detection
Alarm Trigger	Periodic Timer, Intelligent Video and External Digital Input
Alarm Event	Intelligent Video, File Upload via FTP and E-mail, E-mail Notification with Snapshot Attachment, external Output Activation, File Recording to SD Card Remote FTP or Remote NAS
Web Browser	Microsoft IE, Mozilla Firefox, Google Chrome
Local Storage	SD/SDHC Card Support
Casing	IP68, Vandal-proof, Built-in Heater and Fan
Dimension	160(W)×310(H)×425(D)mm
Weight	5800g
Power	Max. 300 W, 24 Vac or 90~240 Vac

I/O Connectors	<ol style="list-style-type: none"> 1. RJ-45 female Type 10base-T/100Base-TX 2. Power Cable 3. Audio Line In/Out 4. Alarm In/Out 5. SD Card Slot 6. Reset
-----------------------	--

Failover	SD/SDHC Auto-Recovery, Reset
Operational Conditions	-40°C~60°C(-40°F~140°F) Humidity : 20%~80%RH
Wireless Support	Yes, Support External 802.11n USB –Wi-Fi Dongle
Included Accessories	QIG, Power Adapter, Power cable, Video Out Cable, CD-ROM(user Manual, Free Bundle NVR), Bracket (3-Axis Bracket Optional)
Approvals	FCC Part 15 Subpart B, CE EN55022 Class B, EN55024, LVD, RoHS
IR range	40M
IR Wavelength	850nm