



DL1058AHD HD720P Turbo HD Bullet Camera



Caractéristiques

	DL1058AHD 2.8~12mm Varifocal
Image Sensor	1/2.9" 1 Megapixel CMOS
Effective Picture (HxV)	1280 x 720
Electronic Shutter	1/60s ~ 1/100,000s
Video Frame Rate	30fps @ 720P
Synchronization	Internal
Min. Illumination	0.01 Lux @ F1.2 (AGC On), 0 Lux (IR On)
Video Output	1-channel BNC HD-over-Coax high definition video output
Max. IR LEDs Length	98ft (30m), Smart IR
Day/Night	Auto (ICR) / B&W / Color
Noise Reduction	2D
Focal Length	2.8~12mm
Angle of View	H: 105.5°~32.9°
Lens Type	Manual / Fixed Iris
Mount Type	Φ14
Power Supply	DC12V±10%
Power Consumption	Max 3.2W
Working Environment	-22°F ~ 140°F (-30°C ~ 60°C) / Less than 95% RH (no condensation)
Transmission Distance	Over 1640ft (500m) via 75-3 coaxial cable
Ingress Protection	IP66
Dimensions	8.4" x 3.2" x 2.83" (213mm x 80mm x 72mm)
Weight	19.4oz (0.55kg)

* La photo du produit et les spécification technique peuvent être modifiées sans préavis.
 Pour plus d'information, s'il vous plaît contacter notre équipe de vente locale.



Key features

- 1/2.9" 1 Megapixel CMOS
- 2.8~12mm Varifocal Lens
- 30fps @ 720P
- High speed, long distance real-time transmission
- Day/Night (ICR), AWB, AGC, BLC, 2D-DNR
- Max IR LEDs length 98 ft, Smart IR
- IP66, IK10, DC12V