



MSE620AHD HD1080P Turbo HD Turret Camera



Caractéristiques

	MSE620AHD
Camera	
Image Sensor	1/3" Progressive Scan SONY
Effective Pixels	1280(H)*720(V)
Min. Illumination	0.01 Lux @(F1.2,AGC ON), 0 Lux with IR
Shutter Time	1/25(1/30) s to 1/50,000 s
Lens	2.8~8mm Varifocal Lens Angle of View: 76.88°(3.6mm), 99.73°(2.8mm), 50.1°(6mm)
Lens Mount	M12
Angle Adjustment	Pan: 0 - 360°, Tilt: 0 - 90°, Rotation: 0 - 360°
Day & Night	ICR
Synchronization	Internal synchronization
Video Frame Rate	1080p@25fps/720p@30fps
HD Video Output	1 Analog HD output
S/N Ratio	More than 52dB
General	
Working Temperature/ Humidity	-40 °C - 60 °C (-40 °F - 140 °F) Humidity 90% or less (non-condensing)
Power Supply	12 VDC
Power Consumption	Max. 3.5W
Weather Proof Ratings	IP66
IR Range	Up to 30m
Dimensions	89.6 × 59.1 mm (3.53" × 2.33")
Weight	120 g

* La photo du produit et les spécification technique peuvent être modifiées sans préavis.
 Pour plus d'information, s'il vous plaît contacter notre équipe de vente locale.



Key features

- HD1080P Video Output
- 2.8~8mm Varifocal Lens
- True Day/Night
- DNR, Smart IR
- 30m IR distance
- IP66 weatherproof